



Guangzhou Yixiu Lvdiان Energy Technology Co.,Ltd

No.3A06, Floor 4, No.1498, Fanghua Road, Renhe Village, Renhe Town, Baiyun district Guangzhou, China
Tel: 86-020-86213109 Phone : +00 86 13068893999 Web: www.eshowcharger.com

Specification of Battery Charger

(All Aluminium case)

**28.8V /40A Lifepo4 BATTERY
CHARGER**





Guangzhou Yixiu Lvian Energy Technology Co.,Ltd

No.3A06, Floor 4, No.1498, Fanghua Road, Renhe Village, Renhe Town, Baiyun district Guangzhou, China
Tel: 86-020-86213109 Phone : +00 86 13068893999 Web: www.eshowcharger.com

1. General

24v Battery Charger 260*175*90mm can work normally under 28.8Vdc /40A 8s lifepo4 batteries

2. Electrical characteristics

2.1 Input characteristic

No.	Model	YX-1500W	备注 Remark
1	Battery	<input type="checkbox"/> Li-ion <input checked="" type="checkbox"/> Lifepo4	8s lifepo4 batteries
2	Max output voltage	28.8V ± 0.2Vdc	
3	Output current	40A ±0.2 A	
4	Actual output power	1152W	
5	Input voltage	200-240vac	As customers' requirement
6.	AC input voltage frequency	50/60 Hz	

2.2 Output characteristic or charge stages

No.	Item	Technical specification	Remark
1	CC(constant current)	40A	
2	CV(constant voltage)	28.8Vdc	
3	Float Charging	No	
4	Transition Current	2.0A	
5	Power efficiency	≥ 80%	Input Voltage =230Vac, rated load



Guangzhou Yixiu Lvian Energy Technology Co.,Ltd

No.3A06, Floor 4, No.1498, Fanghua Road, Renhe Village, Renhe Town, Baiyun district Guangzhou, China
Tel: 86-020-86213109 Phone : +00 86 13068893999 Web: www.eshowcharger.com

YXLN

2.3 Protection characteristics

No.	Item	Technical specification	Remark
1	Over voltage protection	Yes	
2	Software over voltage protection	The charger software limits the maximum output voltage to a level suitable for the connected battery system.	
3	Over temperature protection	Yes	
4	Current limiting protection	Yes	At CC mode
5	Short circuit protection	Short circuit protection should be automatically recovery after remove the condition.	
6	Reverse polarity protection	When output wires are reversely connected to the battery the charger will not operate and will work normally when DC wires are correctly connected.	

2.4 Charging indicator

No.	Item	Status	Remark
1	Power on	LED1: Red	
2	Charging	LED2: Red	
3	Fully charged	LED2: Green	
4	Charging Voltage Display	yes	
5	Charging Current Display	yes	

3.Environmental condition

No.	Item	Technical specification	Remark
1	Operation temperature	-15~+45°C	
2	Humidity	5~95%	
3	Storage temperature	-40~+70°C	
4	Altitude	0~3000m	



Guangzhou Yixiu Lvbian Energy Technology Co.,Ltd

No.3A06, Floor 4, No.1498, Fanghua Road, Renhe Village, Renhe Town, Baiyun district Guangzhou, China
Tel: 86-020-86213109 Phone : +00 86 13068893999 Web: www.eshowcharger.com

4.Safety

No.	Item		Standard (or test condition)	Remark
1	Electric strength test	Input-output	1500Vac/10mA/1min	No breakdown
2	Isolation resistance	Input-ground	$\geq 10\text{Mohm}@500\text{Vdc}$	
		Output-ground	$\geq 10\text{Mohm}@500\text{Vdc}$	
3	Leakage current		$< 5.0\text{mA}$	Input voltage =264Vac

5.Environmental testing requirements

No.	Item	Technical specification	Remark
1	High temperature ambient operating	+40°C	Features OK
2	Low temperature ambient operating	-15°C	Features OK
3	High temperature storage	+70°C	Work normally after recovery under normal temperature for 2 hours
4	Low temperature storage	-40°C	Work normally after recovery under normal temperature for 2 hours

6.Mechanical characteristic:

Shell material: Aluminum

Outline dimension: L*W*H=260×175×90mm

Input socket: meets IEC standard

AC wires: 1.5m length

DC wire: 1.5m length

Net Weight: 4.5 Kg

7.Reliability requirements

No.	Item	Technical specification	Remark
1	MTBF	MTBF no less than 20000 hours (25 degrees C, Full load and rated voltage input)	

Guangzhou Yixiu Lvdiان Energy Technology Co.,Ltd



No.3A06, Floor 4, No.1498, Fanghua Road, Renhe Village, Renhe Town, Baiyun district Guangzhou, China
Tel: 86-020-86213109 Phone : +00 86 13068893999 Web: www.eshowcharger.com

YXLN

2	Burn-in and Life test	At ambient temperature 25 °C aging in two minutes, shell surface temperature ≤ 55 °C.	
---	-----------------------	--	--

8.Charging Curve

